


## DEEP BLUE 4.0



630W n-type Bifacial Double Glass  
High Efficiency Mono Module  
JAM78D40 605-630/GB/1500V Series

### Introduction

Power by the latest MBB n-type solar cell, half-cell configuration and gapless ribbon connection technology, these modules have higher output power, lower LID, better weak illumination response, and better temperature coefficient.



Higher power generation  
better LCOE



Better weak illumination response




Better Temperature Coefficient

### Superior Warranty

- 12-year product warranty
- 30-year linear power output warranty

1% 1st-year Degradation

0.4% Annual Degradation  
Over 30 years



■ n-type Bifacial Double Glass Module Linear Performance Warranty


■ Standard Module Linear Performance Warranty

### Comprehensive Certificates

- IEC 61215, IEC 61730
- ISO 9001: 2015 Quality management systems
- ISO 14001: 2015 Environmental management systems
- ISO 45001: 2018 Occupational health and safety management systems



**MECHANICAL DIAGRAMS**



Remark: customized frame color and cable length available upon request

**SPECIFICATIONS**

Cell	Mono
Weight	33.4kg
Dimensions	2465±2mm×1134±2mm×35±1mm
Cable Cross Section Size	4mm <sup>2</sup> (IEC), 12 AWG(UL)
No. of cells	156(6×26)
Junction Box	IP68, 3 diodes
Connector	Stäubli MC4-EVO2A/MC4-EVO2 QC Solar QC 4.10-35
Cable Length (Including Connector)	Portrait:200mm(+)/300mm(-); Landscape:1500mm(+)/1500mm(-)
Front Glass/Back Glass	2.0mm/2.0mm
Country of Manufacturer	China/Vietnam

**ELECTRICAL PARAMETERS AT STC**

TYPE	JAM78D40-605/GB/1500V	JAM78D40-610/GB/1500V	JAM78D40-615/GB/1500V	JAM78D40-620/GB/1500V	JAM78D40-625/GB/1500V	JAM78D40-630/GB/1500V
Rated Maximum Power(Pmax) [W]	605	610	615	620	625	630
Open Circuit Voltage(Voc) [V]	55.38	55.59	55.79	55.99	56.18	56.38
Maximum Power Voltage(Vmp) [V]	46.86	47.05	47.24	47.43	47.61	47.80
Short Circuit Current(Isc) [A]	13.59	13.64	13.69	13.74	13.79	13.84
Maximum Power Current(Imp) [A]	12.91	12.97	13.02	13.07	13.13	13.18
Module Efficiency [%]	21.6	21.8	22.0	22.2	22.4	22.5
Power Tolerance	0~+5W					
Temperature Coefficient of Isc(α <sub>Isc</sub> )	+0.046%/°C					
Temperature Coefficient of Voc(β <sub>Voc</sub> )	-0.260%/°C					
Temperature Coefficient of Pmax(γ <sub>Pmp</sub> )	-0.300%/°C					
STC	Irradiance 1000W/m <sup>2</sup> , cell temperature 25°C, AM1.5G					

Remark: Electrical data in this catalog do not refer to a single module and they are not part of the offer. They only serve for comparison among different module types. Measurement tolerance at STC: Pmax ±3%, Voc ±3% and Isc ±5%.

**ELECTRICAL CHARACTERISTICS WITH 10% SOLAR IRRADIATION RATIO**

TYPE	JAM78D40-605/GB/1500V	JAM78D40-610/GB/1500V	JAM78D40-615/GB/1500V	JAM78D40-620/GB/1500V	JAM78D40-625/GB/1500V	JAM78D40-630/GB/1500V
Rated Max Power(Pmax) [W]	653	659	664	670	675	680
Open Circuit Voltage(Voc) [V]	55.18	55.38	55.59	55.79	55.99	56.18
Max Power Voltage(Vmp) [V]	46.66	46.86	47.05	47.24	47.43	47.61
Short Circuit Current(Isc) [A]	15.22	15.29	15.37	15.44	15.51	15.57
Max Power Current(Imp) [A]	14.27	14.34	14.42	14.49	14.56	14.62
Irradiation Ratio (rear/front)	10%					


\*For Nexttracker Installations, Maximum Static Load Please Take Compatibility Approve Letter Between JA Solar And Nextacker For Reference  
\*\*Bifaciality=Pmax,rear/Rated Pmax,front

**OPERATING CONDITIONS**


Maximum System Voltage	1500V DC
Operating Temperature	-40°C~+85°C
Maximum Series Fuse Rating	30A
Maximum Static Load,Front* Maximum Static Load,Back*	3600Pa, 1.5 1600Pa, 1.5
NOCT	45±2°C
Bifaciality**	80%±10%
Fire Safety Class	Class C

**CHARACTERISTICS**

Current-Voltage Curve JAM78D40-610/GB/1500V



Power-Voltage Curve JAM78D40-610/GB/1500V



Current-Voltage Curve JAM78D40-610/GB/1500V

